

There is Power Mobility. And then there's

POWERFUL MOBILITY



Features

- ✓ Full suspension and a top speed of 9.3 mph
- ✓ Dual disc brakes with no roll back on inclined surfaces
- ✓ Digital tritium control display with speed, time, temperature, battery usage
- ✓ Running lights and dual mirrors with front facing signal blinkers
- ✓ Aluminum alloy wheel rims



Royale 3

Call 1-800-944-1997 or visit us at www.evrider.com

Royale 3



Digital Display



Thumb and Delta Throttle

Technical Specifications

Dimensions		Performance	
Overall Length	62" in / 157.5 cm	Brake System	Dual Disc w/Roll Back Prevention
Overall Width	29" in / 74 cm - Std Wheels	Climbing Angle	12°
Overall Height	53" in / 135 cm	Charger Type	8 amp / Off-Board 120 / 140 Volt / 50/60 Hz
Seat & Tiller Folded	42.5" in / 108cm - Seat Folded	Charging Time	6 - 8 hrs
Height for Transport - Minimum	36" in / 92 cm	Controller	160 amp / Dynamic Rhino
Ground Clearance	6" in / 15.25 cm	Driving Range	Up to 32 miles / 50 km
Tires		Load Capacity	450 lbs / 205 kgs (8mph / 12 km/h) 350 lbs / 159 kgs (9.3mph / 15 km/h)
Tire Type	Pneumatic Tires	Turning Radius	50" in / 126 cm
Rim Type	Aluminum Alloy	Motor	1300W / 4100RPM / 1.7HP - Brush Motor
Wheelbase	41" / 104 cm	Speed * - Maximum	Up to 15 km/h (9.3 mph) * Opt 12k km/h (8 mph)
OEM Spec	Front: 3.00 - 10 Rear: 100 / 80-10	Features	
Outside Diameter	Front: 16" / 41 cm Rear: 16" / 41 cm	Basket Type & Weight Capacity	Rear: Wire-Vinyl Coated, Rear & Seat Mounted
Width	Front: 3.5" / 9 cm Rear: 4" / 10 cm	Colors	Burgundy Red/Midnight Black/Diamond Silver
Rim Diameter	Front: 10" / 26 cm Rear: 10" / 26 cm	Control - Display Type	Digital Tritium Controls
Max PSI	Front: 36 Back: 36	Leg Room	13" / 32 cm
Weight		Light Type	Running w/mirror-mounted Signal Blinkers
With Batteries	337 lbs / 153 kgs	Seat Type	20" Width - Captain Style
With No Batteries	227 lbs / 103 kgs	Seat Features	Seatbelt & Adjustable Armrests
Shipping Weight - with Bat.	387 lbs / 176 kgs	Seat Swivel	360°
Shipping Weight - No Bat.	277 lbs / 126 kgs	Tiller Type	Infinite Adjustment
Battery		Throttle Control Type	Thumb or Delta
Battery Type (Recommended)	Lead Acid - AGM	Suspension	Full / Independent Front
Battery Power (Recommended)	80Ah / 12V (Two Required)		

(*) Actual range and speed are determined by user weight, battery and terrain conditions.
The above data was calculated using a std. weight of 95 Kg (209 lb) on flat smooth surfaces.

Call **1-800-944-1997** or visit us at **www.evrider.com**